



Product overview - apparatus below the basin

order no.	UB23015	UB23020	UB23030	UB23035	UB23040	UB23060	UB40060	UB40075
assembly place	below basin	below basin	below basin	below basin	below basin	below basin	below basin	below basin
nominal voltage	230 V	230 V	230 V	230 V	230 V	230 V	400 V	400 V
connection power	1,5 kW	2,0 kW	3,0 kW	3,5 kW	4,0 kW	6,0 kW	6,0 kW	7,5 kW
weight	0,7 kg	0,7 kg	0,7 kg	0,7 kg	0,7 kg	0,7 kg	0,7 kg	0,7 kg
height	61 mm	61 mm	61 mm	61 mm	61 mm	61 mm	61 mm	61 mm
width	105 mm	105 mm	105 mm	105 mm	105 mm	105 mm	105 mm	105 mm
depth	205 mm	205 mm	205 mm	205 mm	205 mm	205 mm	205 mm	205 mm
degree of protection	IP 24	IP 24	IP 24	IP 24	IP 24	IP 24	IP 24	IP 24
nominal over pressure	0 bar	0 bar	0 bar	0 bar	0 bar	0 bar	0 bar	0 bar
connector cable	1,5 meter	1,5 meter	1,5 meter	1,5 meter	without *	without *	without *	without *

* From 4 kW upwards, the connection of the apparatus has to be of a fixed, permanent type and with all poles separable from the current supply (using circuit breaker or individual fuse).

Please adhere to the document about the amount of water outlet. This document helps you to find out what power your heater needs in order to meet your requirements.

Optional: Electronic security switch for protecting the apparatus from running dry. The heater only turns on if there is enough water flow. No fusing of the heating in case of water shortage. Available for all heaters up to 4 kW connection power – order number: E. Find more information in our electronic flyer.
Pipe connection for caravans – order number: WW (it is necessary to order the electronic with the connection).

examples of application

